

CAST Y STRAINER

Class 600 LBS

Basic design features

Design	ASME B16.34
Face to face	B16,10
Flanges	ASME B16.5
Testing	API 598
Bore	FULL
Bonnet	BOLTED
Marking	CE - PED
Certificates	EN 10204 - 3.1 / 3.2
Rating	600 LBS

Test Pressure to API 598

Class	600 LBS
Shell (Water)	153 bar
Seat (Water)	-
Seat (Air)	6.0 bar

BILL OF MATERIALS STANDARD ACCORDING TO ASTM

	PART NAME	WCB	LCC	CF8M
1	BODY	ASTM A 216 WCB	ASTM A352 LCC	ASTM A351 CF8M
2	COVER	ASTM A 216 WCB	ASTM A352 LCC	ASTM A351 CF8M
3	GASKET	316+GRAPHITE	316+GRAPHITE	316+GRAPHITE
4	PLUG	ASTM A 105	ASTM 316SS	ASTM 316
5	SCREEN	ASTM 316SS	316 SS	STM 316SS
6	BOLT	ASTM A193 B7M	ASTM A193 L7M	ASTM A193 B8
7	NUT	ASTM A 194 2HM	ASTM A194 7M	ASTM A 194 8

Body Material available in: LCB-C5-C12-WC6-WC9-C12A-CF8-CF3-CF3M

*Standard Drain Plug: ½ - 1 ½ DRAIN ½NPT

*Standard Drain Plug: ► 2" DRAIN ¾ NPT

*Standard Screen: Mesh 0,8 ½ for 1 ½-

*Standard Screen: Mesh 1,5 ► 2"

On request Screen: 304-316-MONEL

This document is the property of OPM ITALIA Srl. It must not be stored, reproduced or disclosed to others without Our written authorisation.

All data, subject to technical changes, are only for information and not for official use



CAST Y STRAINER

Class 600 LBS

SIZE INCH	L (MM)	H(MM)	ØD(MM)
1/2	/	/	/
3/4	/	/	/
1	/	/	/
1 1/2	/	/	/
2	292	197	165
2 1/2	330	213	190
3	356	255	210
4	432	320	275
6	559	378	355

O.P.M. ITALIA Srl Via Murri, 40 20013 Magenta - MI Italy Phone +39 02 97003091
www.opmitalia.com / email : info@opmitalia.com